

# KPC251, KPC255

## REGULAR CAMERA



### ● OVERVIEW

This surveillance camera series is designed to suit versatile security demand. With the HIGH QUALITY PERFORMANCE and UNMATCHED LOW PRICE, it makes your security demand affordable.

### ● FEATURES

- (1) 1/3" SONY Super HAD Color CCD image sensor
- (2) Standard resolution
- (3) Low light sensitivity of 0.5 Lux at F2.0
- (4) Built-in microphone
- (5) High reliability under long time operation

### ● SPECIFICATIONS\*

Model	KPC251	KPC255	
Pick up Element	1/3" SONY Super HAD Color CCD image sensor		
Number of Pixel	510(H)x492(V) <NTSC> / 500(H)x582(V) <PAL>		
Resolution	Standard Resolution		
Minimum illumination	0.5 Lux / F2.0		
S/N Ratio	More than 48dB (AGC off)		
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.		
Lens Mount	CS or C Mount		
IRIS Mode	AES / VD / DD		
Gain Control	Normal / Max selectable		
Flickerless	On / Off selectable		
White Balance	ATW		
Video Output	1.0Vp-p composite, 75Ω		
Power Source	DC12V ± 10%	AC230V	AC24V / DC12V
Current Consumption	95mA	2.8W Max	
Dimension (mm)**	117(L) x 60(W) x 50(H)		
Weight	250g	430g	300g

\* The specification is subject to change without notice.

\*\* Dimensional Tolerance: ± 5mm